

Sub 8
C1 334. (Amended) The implement of Claim 328, wherein the shells in said first position are at least partly arranged in spaced apart relationship and in said first position form an interspace therebetween, said interspace being open to at least one end of the implement and forming a slot for material to be processed by said stapler and said puncher, respectively.

25
C2 351. (Amended) The implement of Claim 327, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided.

55
C3 467. (Amended) The implement of Claim 327, wherein at least one of the members comprises adjacent channels extending in a longitudinal direction of the member, wherein in one of said channels functional elements of said stapler and said puncher, respectively, are disposed, and wherein in at least one channel said additional tools are disposed.

57
530. (New) The implement of Claim 327, wherein the at least one additional tool is provided in the one of said first and second members comprising the staple anvil of said stapler and the hole die of said puncher, respectively.

64
C4 531. (New) The implement of Claim 524, wherein the first and second members each comprise a hollow outer shell with a circumferential contour defining a respective base surface.

63
64 532. (New) The implement of Claim 531, wherein the circumferential contours of the hollow shells of the first and second members when in the first position face one another.

66
64 533. (New) The implement of Claim 531, wherein the shells in said first position are arranged in substantial mirror symmetry so that the contours of the shells are substantially aligned.

Sub E1
64
534. (New) The implement of Claim 531, wherein each shell comprises a pair of substantially plane lateral surfaces extending substantially orthogonally to the base surface, and top and front surfaces having rounded contours.

68
535. (New) The implement of Claim 524, wherein one of said members has an outer contour comprising a flattened section.

64
536. (New) The implement of Claim 531, wherein in said first position the two base surfaces are spaced apart.

CH
70
537. (New) The implement of Claim 531, wherein the shells in said first position are at least partly arranged in spaced apart relationship and in said first position form an interspace therebetween, said interspace being open to at least one end of the implement and forming a slot for material to be processed by said puncher.

71
538. (New) The implement of Claim 524, wherein one of said first and second members in said first position is received at least partially in the other of said first and second members.

72
539. (New) The implement of Claim 524, wherein one of said members comprises a recess into which at least a part of the other of said members is displaceable.

73
540. (New) The implement of Claim 538, wherein, in said first position, respective outer contours of said members are substantially flush.

74
541. (New) The implement of Claim 538, wherein an insertion slot for receiving material to be processed is provided in the one of said first and second members comprising the hole die of said puncher.

75
542. (New) The implement of Claim 534, wherein the lateral surfaces of at least one member are depressed relative to the contours of the top and front surfaces.

76
543. (New) The implement of Claim 531, wherein at least one of the members comprises a metallic core and a plastic cover cap mounted on said core.

77
Sub
91
544. (New) The implement of Claim 543, wherein said at least one core is U-shaped and comprises a U-base and a pair of U-legs, the U-base forming the base surface and the U-legs defining the lateral surfaces of the respective member.

78
545. (New) The implement of Claim 534, wherein at least one actuating element is disposed on at least one of the lateral surfaces.

79
546. (New) The implement of Claim 545, wherein the at least one actuating element is substantially flush with the contours of a top and end surface of the member provided with the at least one actuating element.

C4
80
547. (New) The implement of Claim 531, wherein the members are interconnected adjacent a frontal surface by means of a pivot, the axis of which extends orthogonal to a longitudinal axis and parallel to the base surfaces of said members.

81
548. (New) The implement of Claim 547, wherein one of the members comprises a bearing bracket which extends into a hollow space of the other member wherein said pivot is disposed.

82
549. (New) The implement of Claim 524, wherein one of said members forms a lever-like actuator for the puncher.

83
550. (New) The implement of Claim 524, wherein said members are spring biased into the second position which is defined by stops.

84
551. (New) The implement of Claim 550, wherein the stops are inactivatable.

85
552. (New) The implement of Claim 524, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided.

86
553. (New) The implement of Claim 552, wherein said locking element includes a manually operated actuator.

Sub
E1
87
554. (New) The implement of Claim 553, wherein said actuator comprises a slider switch.

88
555. (New) The implement of Claim 553, wherein said actuator is disposed at a top surface of the one of said members including the locking element.

89
556. (New) The implement of Claim 553, wherein the members are interconnected by a pivot adjacent one end of the members, and wherein said actuator is disposed adjacent the other end of the members.

C4
90
557. (New) The implement of Claim 552, wherein the locking element is displaceable parallel to a top surface of the respective member.

91
558. (New) The implement of Claim 552, wherein said other of said members comprises a bracket, and wherein the bracket comprises the locking receiver.

92
559. (New) The implement of Claim 524, wherein at least one of said members is provided with a cavity for receiving said at least one additional tool in its storing position.

93
560. (New) The implement of Claim 524, wherein the at least one additional tool is slideably disposed in at least one of the members.

94
561. (New) The implement of Claim 560, wherein the at least one additional tool comprises a slide-action locking bar which is actuable from the exterior.

95
562. (New) The implement of Claim 524, wherein a plurality of additional tools are disposed parallel to a longitudinal extension of the members.

96
563. (New) The implement of Claim 560, wherein the at least one member comprises slots at at least one of its end surfaces, said at least one additional tool being slidable through said slots into its working positions.

97
564. (New) The implement of Claim 560, wherein said at least one additional tool has a guiding shank provided at its rear end with respect to the telescoping direction.

98

565. (New) The implement of Claim 564, wherein a longitudinal guide for said guiding shank is provided.

97

99

566. (New) The implement of Claim 565, wherein the guiding shank is provided with a sliding block.

98

100

567. (New) The implement of Claim 560, wherein the at least one additional tool is slidable along one of its top and lateral surfaces of the corresponding member.

93

101

568. (New) The implement of Claim 524, wherein the at least one additional tool is pivotably connected with the at least one of said members such that it is pivotable out of said member into its working position.

62

102

569. (New) The implement of Claim 524, wherein at least one removable tool is disposed in at least one of the members and is removable from said member.

62

103

570. (New) The implement of Claim 524, wherein the at least one additional tool is spring-biased in at least one of its storing and working positions.

62

104

571. (New) The implement of Claim 524, wherein the at least one additional tool is releasably lockable in at least one of its storing and working positions.

62

105

572. (New) The implement of Claim 571, wherein the at least one additional tool is lockable via a catch.

104

106

573. (New) The implement of Claim 571, further comprising an actuator for unlocking at least one of said additional tools.

104

107

574. (New) The implement of Claim 560, wherein slots are provided for said slide-action locking bars.

108

575. (New) The implement of Claim 571, wherein slots are provided for keys for releasably locking said tool.

104

109

576. (New) The implement of Claim 573, wherein the actuator is movable in a slot in one of the top and lateral surfaces of said member taking up said additional tool.

106

110
577. (New) The implement of Claim 573, wherein said actuator is operative to unlock a plurality of said additional tools.

Sub E1
111
578. (New) The implement of Claim 524, wherein said at least one additional tool comprises a tool selected from the group consisting of a scissors, a knife blade, a cutter, a staple remover, a screw driver, an extendable pointer, a magnifier, and a rule.

112
579. (New) The implement of Claim 524, wherein at least one of the members comprises adjacent channels extending in a longitudinal direction of the member, wherein in one of said channels functional elements of said puncher are disposed, and wherein in at least one channel said additional tools are disposed.

113
580. (New) The implement of claim 524, wherein said elongated body is substantially closed.

C4
114
581. (New) The implement of Claim 524, wherein the at least one additional tool is provided in the one of said first and second members comprising the hole die of said puncher.

115
582. (New) A multipurpose handheld implement comprising:

a first member and a second member, said first and second members being connected together to move between a first position, in which they form an elongated body, and a second position;

wherein said first and second members comprise at least one of the tools of a group of a stapler and a puncher, said stapler comprising a staple magazine, a staple driver and a staple anvil of a stapler and said puncher comprising a punch, a hole die and a lever, said lever being positioned to actuate the punch;

wherein said first and second members when in the second position form an interspace to receive a workpiece for processing by one of the stapler and the puncher as the first and second members are moved relative to each other;

Sub
E1
wherein at least one of said members further comprises at least one additional tool in a storing position from which the at least one additional tool is movable into a working position;

wherein said first and second members have substantially mirror symmetrical outer contours and form a grip for handling said at least one additional tool when in the first position in which said members are substantially aligned.

116
583. (New) The implement of Claim 582, wherein the first and second members each comprise a hollow outer shell with a circumferential contour defining a respective base surface.

117
584. (New) The implement of Claim 583, wherein the circumferential contours of the hollow shells of the first and second members when in the first position face one another.

C4
118
585. (New) The implement of Claim 583, wherein the shells in said first position are arranged in substantial mirror symmetry so that the contours of the shells are substantially aligned.

119
586. (New) The implement of Claim 583, wherein each shell comprises a pair of substantially plane lateral surfaces extending substantially orthogonally to the base surface, and top and front surfaces having rounded contours.

120
587. (New) The implement of Claim 582, wherein one of said members has an outer contour comprising a flattened section.

121
588. (New) The implement of Claim 583, wherein in said first position the two base surfaces are spaced apart.

122
589. (New) The implement of Claim 583, wherein the shells in said first position are at least partly arranged in spaced apart relationship and in said first position form an interspace therebetween, said interspace being open to at least one end of the implement and forming a slot for material to be processed by said stapler and said puncher, respectively.

123
590. (New) The implement of Claim 582, wherein one of said first and second members in said first position is received at least partially in the other of said first and second members.

Sub E1
124
591. (New) The implement of Claim 582, wherein one of said members comprises a recess into which at least a part of the other of said members is displaceable.

125
592. (New) The implement of Claim 590, wherein, in said first position, respective outer contours of said members are substantially flush.

126
593. (New) The implement of Claim 590, wherein an insertion slot for receiving material to be processed is provided in the one of said first and second members comprising the staple anvil of said stapler.

C4
127
594. (New) The implement of Claim 590, wherein an insertion slot for receiving material to be processed is provided in the one of said first and second members comprising the hole die of said puncher.

128
595. (New) The implement of Claim 586, wherein the lateral surfaces of at least one member are depressed relative to the contours of the top and front surfaces.

129
596. (New) The implement of Claim 583, wherein at least one of the members comprises a metallic core and a plastic cover cap mounted on said core.

130
597. (New) The implement of Claim 596, wherein said at least one core is U-shaped and comprises a U-base and a pair of U-legs, the U-base forming the base surface and the U-legs defining the lateral surfaces of the respective member.

131
598. (New) The implement of Claim 586, wherein at least one actuating element is disposed on at least one of the lateral surfaces.

132
599. (New) The implement of Claim 598, wherein the at least one actuating element is substantially flush with the contours of a top and end surface of the member provided with the at least one actuating element.

133
600. (New) The implement of Claim 583, wherein the members are interconnected adjacent a frontal surface by means of a pivot, the axis of which extends orthogonal to a longitudinal axis and parallel to the base surfaces of said members.

Sub
E1
134
601. (New) The implement of Claim 600, wherein one of the members comprises a bearing bracket which extends into a hollow space of the other member wherein said pivot is disposed.

135
602. (New) The implement of Claim 582, wherein one of said members forms a lever-like actuator for the stapler.

136
603. (New) The implement of Claim 582, wherein one of said members forms a lever-like actuator for the puncher.

137
604. (New) The implement of Claim 582, wherein said members are spring biased into the second position which is defined by stops.

C4
138
605. (New) The implement of Claim 604, wherein the stops are inactivatable.

139
606. (New) The implement of Claim 582, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein said locking element includes a manually operated actuator.

140
607. (New) The implement of Claim 606, wherein said actuator comprises a slider switch.

141
608. (New) The implement of Claim 606, wherein said actuator is disposed at a top surface of the one of said members including the locking element.

142
609. (New) The implement of Claim 606, wherein the members are interconnected by a pivot adjacent one end of the members, and wherein said actuator is disposed adjacent the other end of the members.

143
610. (New) The implement of Claim 582, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is

provided, and wherein the locking element is displaceable parallel to a top surface of the respective member.

Sub E1
144 115
611. (New) The implement of Claim 582, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein said other of said members comprises a bracket, and wherein the bracket comprises the locking receiver.

145 115
612. (New) The implement of Claim 582, further comprising means for selectively activating and deactivating the stapler.

94
148 115
613. (New) The implement of Claim 582, further comprising means for automatically deactivating the stapler after each stapling operation so that when the first and second members are in the first position after said stapling operation the stapler is inactive; and means for manually activating the stapler after deactivation by said deactivating means.

147 115
614. (New) The implement of Claim 582,
wherein one of said members comprises a first activating mechanism for activating said stapler, and a second activating mechanism for releasing said latch; and wherein the first and second activating mechanisms are manually operable from at least one position external to said one of the members.

148 147
615. (New) The implement of Claim 614, wherein each of said first and second activating mechanisms comprises a manually operated actuator.

149 145
616. (New) The implement of Claim 612, wherein the first activating mechanism is located within an area adjacent to said staple driver.

150 148
617. (New) The implement of Claim 615, wherein said member comprises a top surface, a pair of lateral surfaces and a pair of end surfaces, the actuator for activating said stapler being provided at the end surface adjacent to the staple driver and the actuator for activating said latch being positioned at the top surface.

151

618. (New) The implement of Claim 582, wherein at least one of said members is provided with a cavity for receiving said at least one additional tool in its storing position.

152

619. (New) The implement of Claim 582, wherein the at least one additional tool is slideably disposed in at least one of the members.

153

620. (New) The implement of Claim 619, wherein the at least one additional tool comprises a slide-action locking bar which is actuatable from the exterior.

154

621. (New) The implement of Claim 582, wherein a plurality of additional tools are disposed parallel to a longitudinal extension of the members.

155

622. (New) The implement of Claim 619, wherein the at least one member comprises slots at at least one of its end surfaces, said at least one additional tool being slidable through said slots into its working positions.

156

623. (New) The implement of Claim 619, wherein said at least one additional tool has a guiding shank provided at its rear end with respect to the telescoping direction.

157

624. (New) The implement of Claim 623, wherein a longitudinal guide for said guiding shank is provided.

158

625. (New) The implement of Claim 624, wherein the guiding shank is provided with a sliding block.

159

626. (New) The implement of Claim 619, wherein the at least one additional tool is slidable along one of its top and lateral surfaces of the corresponding member.

160

627. (New) The implement of Claim 582, wherein the at least one additional tool is pivotably connected with the at least one of said members such that it is pivotable out of said member into its working position.

161

628. (New) The implement of Claim 582, wherein at least one removable tool is disposed in at least one of the members and is removable from said member.

Sub E1
162 113
629. (New) The implement of Claim 582, wherein the at least one additional tool is spring-biased in at least one of its storing and working positions.

163 115
630. (New) The implement of Claim 582, wherein the at least one additional tool is releasably lockable in at least one of its storing and working positions.

164 163
631. (New) The implement of Claim 630, wherein the at least one additional tool is lockable via a catch.

165 163
632. (New) The implement of Claim 630, further comprising an actuator for unlocking at least one of said additional tools.

166 158
633. (New) The implement of Claim 619, wherein slots are provided for said slide-action locking bars.

167 163
634. (New) The implement of Claim 630, wherein slots are provided for keys for releasably locking said tool.

168 165
635. (New) The implement of Claim 632, wherein the actuator is movable in a slot in one of the top and lateral surfaces of said member taking up said additional tool.

169 165
636. (New) The implement of Claim 632, wherein said actuator is operative to unlock a plurality of said additional tools.

170 115
637. (New) The implement of Claim 582, wherein said at least one additional tool comprises a tool selected from the group consisting of a scissors, a knife blade, a cutter, a staple remover, a screw driver, an extendable pointer, a magnifier, and a rule.

171 115
638. (New) The implement of Claim 582, wherein at least one of the members comprises adjacent channels extending in a longitudinal direction of the member, wherein in one of said channels functional elements of said stapler and said puncher, respectively, are disposed, and wherein in at least one channel said additional tools are disposed.

179

639. (New) The implement of claim 582, wherein said elongated body is substantially closed.

115

173

640. (New) The implement of Claim 582, wherein the at least one additional tool is provided in the one of said first and second members comprising the staple anvil of said stapler and the hole die of said puncher, respectively.

118

174

641. (New) The implement of Claim 582, comprising means for releasably holding the first and second members in the first position.

115

175

642. (New) The implement of Claim 641, wherein said means comprises a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member.

174

176

643. (New) A multipurpose handheld implement comprising:

a first member and a second member, said first and second members being connected together to move about an axis between a first position, in which they form an elongated body, and a second position;

wherein said first and second members comprise at least one of the tools of a group of a stapler and a puncher, said stapler comprising a staple magazine, a staple driver and a staple anvil of a stapler and said puncher comprising a punch, a hole die and a lever, said lever being positioned to actuate the punch;

wherein said first and second members when in the second position form an interspace to receive a workpiece for processing by one of the stapler and the puncher as the first and second members are moved relative to each other;

wherein at least one of said members further comprises at least one additional bladelike tool in a storing position from which it is movable into a working position, said at least one additional tool having a broadside lying within a radial plane of said axis;

wherein said first and second members in the first position form a grip for handling said at least one additional bladelike tool in its working position.

179

644. (New) The implement of Claim 643, wherein the first and second members each comprise a hollow outer shell with a circumferential contour defining a respective base surface.

178

645. (New) The implement of Claim 644, wherein the circumferential contours of the hollow shells of the first and second members when in the first position face one another.

179

646. (New) The implement of Claim 644, wherein the shells in said first position are arranged in substantial mirror symmetry so that the contours of the shells are substantially aligned.

180

647. (New) The implement of Claim 644, wherein each shell comprises a pair of substantially plane lateral surfaces extending substantially orthogonally to the base surface, and top and front surfaces having rounded contours.

181

648. (New) The implement of Claim 643, wherein one of said members has an outer contour comprising a flattened section.

182

649. (New) The implement of Claim 644, wherein in said first position the two base surfaces are spaced apart.

183

650. (New) The implement of Claim 644, wherein the shells in said first position are at least partly arranged in spaced apart relationship and in said first position form an interspace therebetween, said interspace being open to at least one end of the implement and forming a slot for material to be processed by said stapler and said puncher, respectively.

184

651. (New) The implement of Claim 643, wherein one of said first and second members in said first position is received at least partially in the other of said first and second members.

185

652. (New) The implement of Claim 643, wherein one of said members comprises a recess into which at least a part of the other of said members is displaceable.

186

653. (New) The implement of Claim 651, wherein, in said first position, respective outer contours of said members are substantially flush.

187

654. (New) The implement of Claim 651, wherein an insertion slot for receiving material to be processed is provided in the one of said first and second members comprising the staple anvil of said stapler.

188

655. (New) The implement of Claim 651, wherein an insertion slot for receiving material to be processed is provided in the one of said first and second members comprising the hole die of said puncher.

189

656. (New) The implement of Claim 647, wherein the lateral surfaces of at least one member are depressed relative to the contours of the top and front surfaces.

190

657. (New) The implement of Claim 644, wherein at least one of the members comprises a metallic core and a plastic cover cap mounted on said core.

191

658. (New) The implement of Claim 657, wherein said at least one core is U-shaped and comprises a U-base and a pair of U-legs, the U-base forming the base surface and the U-legs defining the lateral surfaces of the respective member.

192

659. (New) The implement of Claim 647, wherein at least one actuating element is disposed on at least one of the lateral surfaces.

193

660. (New) The implement of Claim 659, wherein the at least one actuating element is substantially flush with the contours of a top and end surface of the member provided with the at least one actuating element.

194

661. (New) The implement of Claim 644, wherein the members are interconnected adjacent a frontal surface by means of a pivot, the axis of which extends orthogonal to a longitudinal axis and parallel to the base surfaces of said members.

195

662. (New) The implement of Claim 661, wherein one of the members comprises a bearing bracket which extends into a hollow space of the other member wherein said pivot is disposed.

198

17B

663. (New) The implement of Claim 643, wherein one of said members forms a lever-like actuator for the stapler.

194

17B

664. (New) The implement of Claim 643, wherein one of said members forms a lever-like actuator for the puncher.

198

17B

665. (New) The implement of Claim 643, wherein said members are spring biased into the second position which is defined by stops.

198

198

666. (New) The implement of Claim 665, wherein the stops are inactivatable.

200

17B

667. (New) The implement of Claim 643, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein said locking element includes a manually operated actuator.

201

200

668. (New) The implement of Claim 667, wherein said actuator comprises a slider switch.

202

200

669. (New) The implement of Claim 667, wherein said actuator is disposed at a top surface of the one of said members including the locking element.

203

200

670. (New) The implement of Claim 667, wherein the members are interconnected by a pivot adjacent one end of the members, and wherein said actuator is disposed adjacent the other end of the members.

204

17B

671. (New) The implement of Claim 643, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein the locking element is displaceable parallel to a top surface of the respective member.

205

17B

672. (New) The implement of Claim 643, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein said other of said members comprises a bracket, and wherein the bracket comprises the locking receiver.

206

17B

673. (New) The implement of Claim 643, further comprising means for selectively activating and deactivating the stapler.

207

17B

674. (New) The implement of Claim 643, further comprising means for automatically deactivating the stapler after each stapling operation so that when the first and second members are in the first position after said stapling operation the stapler is inactive; and means for manually activating the stapler after deactivation by said deactivating means.

208

17B

675. (New) The implement of Claim 643, wherein one of said members comprises a first activating mechanism for activating said stapler, and a second activating mechanism for releasing said latch; and wherein the first and second activating mechanisms are manually operable from at least one position external to said one of the members.

209

20B

676. (New) The implement of Claim 675, wherein each of said first and second activating mechanisms comprises a manually operated actuator.

210

20B

677. (New) The implement of Claim 673, wherein the first activating mechanism is located within an area adjacent to said staple driver.

211

209

678. (New) The implement of Claim 676, wherein said member comprises a top surface, a pair of lateral surfaces and a pair of end surfaces, the actuator for activating said stapler being provided at the end surface adjacent to the staple driver and the actuator for activating said latch being positioned at the top surface.

212

17B

679. (New) The implement of Claim 643, wherein at least one of said members is provided with a cavity for receiving said at least one additional tool in its storing position.

213

17B

680. (New) The implement of Claim 643, wherein the at least one additional tool is slideably disposed in at least one of the members.

214

21B

681. (New) The implement of Claim 680, wherein the at least one additional tool comprises a slide-action locking bar which is actuable from the exterior.

215

176

682. (New) The implement of Claim 643, wherein a plurality of additional tools are disposed parallel to a longitudinal extension of the members.

216

213

683. (New) The implement of Claim 680, wherein the at least one member comprises slots at at least one of its end surfaces, said at least one additional tool being slidable through said slots into its working positions.

217

213

684. (New) The implement of Claim 680, wherein said at least one additional tool has a guiding shank provided at its rear end with respect to the telescoping direction.

218

217

685. (New) The implement of Claim 684, wherein a longitudinal guide for said guiding shank is provided.

219

218

686. (New) The implement of Claim 685, wherein the guiding shank is provided with a sliding block.

220

213

687. (New) The implement of Claim 680, wherein the at least one additional tool is slidable along one of its top and lateral surfaces of the corresponding member.

221

176

688. (New) The implement of Claim 643, wherein the at least one additional tool is pivotably connected with the at least one of said members such that it is pivotable out of said member into its working position.

222

176

689. (New) The implement of Claim 643, wherein at least one removable tool is disposed in at least one of the members and is removable from said member.

223

176

690. (New) The implement of Claim 643, wherein the at least one additional tool is spring-biased in at least one of its storing and working positions.

224

176

691. (New) The implement of Claim 643, wherein the at least one additional tool is releasably lockable in at least one of its storing and working positions.

225

224

692. (New) The implement of Claim 691, wherein the at least one additional tool is lockable via a catch.

226

224

693. (New) The implement of Claim 691, further comprising an actuator for unlocking at least one of said additional tools.

229

213

694. (New) The implement of Claim 680, wherein slots are provided for said slide-action locking bars.

228

224

695. (New) The implement of Claim 691, wherein slots are provided for keys for releasably locking said tool.

229

228

696. (New) The implement of Claim 693, wherein the actuator is movable in a slot in one of the top and lateral surfaces of said member taking up said additional tool.

230

228

697. (New) The implement of Claim 693, wherein said actuator is operative to unlock a plurality of said additional tools.

231

176

698. (New) The implement of Claim 643, wherein said at least one additional bladelike tool comprises a tool selected from the group consisting of a scissors, a knife, a cutter, a staple remover, a screw driver, a magnifier, and a rule.

232

176

699. (New) The implement of Claim 643, wherein at least one of the members comprises adjacent channels extending in a longitudinal direction of the member, wherein in one of said channels functional elements of said stapler and said puncher, respectively, are disposed, and wherein in at least one channel said additional tools are disposed.

233

176

700. (New) The implement of claim 643, wherein said elongated body is substantially closed.

234

176

701. (New) The implement of Claim 643, wherein the at least one additional tool is provided in the one of said first and second members comprising the staple anvil of said stapler and the hole die of said puncher, respectively.

235

176

702. (New) The implement of Claim 643, comprising means for releasably holding the first and second members in the first position.

236

703. (New) The implement of Claim 702, wherein said means comprises a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member.

237

704. (New) A multipurpose handheld implement comprising:

a first member and a second member, said first and second members being connected together to move between a first position, in which they form an elongated body, and a second position;

wherein said first and second members comprise at least one of the tools of a group of a stapler and a puncher, said stapler comprising a staple magazine, a staple driver and a staple anvil of a stapler and said puncher comprising a punch, a hole die and a lever, said lever being positioned to actuate the punch;

wherein said first and second members when in the second position form an interspace to receive a workpiece for processing by one of the stapler and the puncher as the first and second members are moved relative to each other;

wherein at least one of said members further comprises at least two additional tools in a storing position in a substantially parallel manner in longitudinal direction of the body from which storing position the additional tools are movable into a working position by the same kind of motion; and

wherein said first and second members in the first position form a grip for handling all of the additional tools in their working position.

238

705. (New) The implement of Claim 704, wherein the first and second members each comprise a hollow outer shell with a circumferential contour defining a respective base surface.

239

706. (New) The implement of Claim 705, wherein the circumferential contours of the hollow shells of the first and second members when in the first position face one another.

240

238

707. (New) The implement of Claim 705, wherein the shells in said first position are arranged in substantial mirror symmetry so that the contours of the shells are substantially aligned.

241

238

708. (New) The implement of Claim 705, wherein each shell comprises a pair of substantially plane lateral surfaces extending substantially orthogonally to the base surface, and top and front surfaces having rounded contours.

242

239

709. (New) The implement of Claim 704, wherein one of said members has an outer contour comprising a flattened section.

243

238

710. (New) The implement of Claim 705, wherein in said first position the two base surfaces are spaced apart.

244

238

711. (New) The implement of Claim 705, wherein the shells in said first position are at least partly arranged in spaced apart relationship and in said first position form an interspace therebetween, said interspace being open to at least one end of the implement and forming a slot for material to be processed by said stapler and said puncher, respectively.

245

239

712. (New) The implement of Claim 704, wherein one of said first and second members in said first position is received at least partially in the other of said first and second members.

246

239

713. (New) The implement of Claim 704, wherein one of said members comprises a recess into which at least a part of the other of said members is displaceable.

247

245

714. (New) The implement of Claim 712, wherein, in said first position, respective outer contours of said members are substantially flush.

248

245

715. (New) The implement of Claim 712, wherein an insertion slot for receiving material to be processed is provided in the one of said first and second members comprising the staple anvil of said stapler.

249

248

Sub
E1
716. (New) The implement of Claim 712, wherein an insertion slot for receiving material to be processed is provided in the one of said first and second members comprising the hole die of said puncher.

250

248

717. (New) The implement of Claim 708, wherein the lateral surfaces of at least one member are depressed relative to the contours of the top and front surfaces.

251

238

718. (New) The implement of Claim 705, wherein at least one of the members comprises a metallic core and a plastic cover cap mounted on said core.

252

258

719. (New) The implement of Claim 718, wherein said at least one core is U-shaped and comprises a U-base and a pair of U-legs, the U-base forming the base surface and the U-legs defining the lateral surfaces of the respective member.

253

248

720. (New) The implement of Claim 708, wherein at least one actuating element is disposed on at least one of the lateral surfaces.

254

253

721. (New) The implement of Claim 720, wherein the at least one actuating element is substantially flush with the contours of a top and end surface of the member provided with the at least one actuating element.

255

238

722. (New) The implement of Claim 705, wherein the members are interconnected adjacent a frontal surface by means of a pivot, the axis of which extends orthogonal to a longitudinal axis and parallel to the base surfaces of said members.

256

255

723. (New) The implement of Claim 722, wherein one of the members comprises a bearing bracket which extends into a hollow space of the other member wherein said pivot is disposed.

257

239

724. (New) The implement of Claim 704, wherein one of said members forms a lever-like actuator for the stapler.

258

239

725. (New) The implement of Claim 704, wherein one of said members forms a lever-like actuator for the puncher.

259

239

726. (New) The implement of Claim 704, wherein said members are spring biased into the second position which is defined by stops.

260

259

727. (New) The implement of Claim 726, wherein the stops are inactivatable.

268

239

728. (New) The implement of Claim 704, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein said locking element includes a manually operated actuator.

268

268

729. (New) The implement of Claim 728, wherein said actuator comprises a slider switch.

263

268

730. (New) The implement of Claim 728, wherein said actuator is disposed at a top surface of the one of said members including the locking element.

264

268

731. (New) The implement of Claim 728, wherein the members are interconnected by a pivot adjacent one end of the members, and wherein said actuator is disposed adjacent the other end of the members.

265

239

732. (New) The implement of Claim 704, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein the locking element is displaceable parallel to a top surface of the respective member.

268

239

733. (New) The implement of Claim 704, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein said other of said members comprises a bracket, and wherein the bracket comprises the locking receiver.

269

239

734. (New) The implement of Claim 704, further comprising means for selectively activating and deactivating the stapler.

268

239

735. (New) The implement of Claim 704, further comprising means for automatically deactivating the stapler after each stapling operation so that when the first and second members are in the first position after said stapling operation the stapler is inactive; and

means for manually activating the stapler after deactivation by said deactivating means.

269 239
736. (New) The implement of Claim 704,

wherein one of said members comprises a first activating mechanism for activating said stapler, and a second activating mechanism for releasing said latch; and

wherein the first and second activating mechanisms are manually operable from at least one position external to said one of the members.

270 269
737. (New) The implement of Claim 736, wherein each of said first and second activating mechanisms comprises a manually operated actuator.

271 269
738. (New) The implement of Claim 734, wherein the first activating mechanism is located within an area adjacent to said staple driver.

272 270
739. (New) The implement of Claim 737, wherein said member comprises a top surface, a pair of lateral surfaces and a pair of end surfaces, the actuator for activating said stapler being provided at the end surface adjacent to the staple driver and the actuator for activating said latch being positioned at the top surface.

273 239
740. (New) The implement of Claim 704, wherein at least one of said members is provided with a cavity for receiving said at least one additional tool in its storing position.

274 239
741. (New) The implement of Claim 704, wherein the at least one additional tool is slideably disposed in at least one of the members.

275 274
742. (New) The implement of Claim 741, wherein the at least one additional tool comprises a slide-action locking bar which is actuatable from the exterior.

276 239
743. (New) The implement of Claim 704, wherein a plurality of additional tools are disposed parallel to a longitudinal extension of the members.

277 274
744. (New) The implement of Claim 741, wherein the at least one member comprises slots at at least one of its end surfaces, said at least one additional tool being slidable through said slots into its working positions.

278

745. (New) The implement of Claim 741, wherein said at least one additional tool has a guiding shank provided at its rear end with respect to the telescoping direction.

279

746. (New) The implement of Claim 745, wherein a longitudinal guide for said guiding shank is provided.

280

747. (New) The implement of Claim 746, wherein the guiding shank is provided with a sliding block.

281

748. (New) The implement of Claim 741, wherein the at least one additional tool is slidable along one of its top and lateral surfaces of the corresponding member.

282

749. (New) The implement of Claim 704, wherein the at least one additional tool is pivotably connected with the at least one of said members such that it is pivotable out of said member into its working position.

283

750. (New) The implement of Claim 704, wherein at least one removable tool is disposed in at least one of the members and is removable from said member.

284

751. (New) The implement of Claim 704, wherein the at least one additional tool is spring-biased in at least one of its storing and working positions.

285

752. (New) The implement of Claim 704, wherein the at least one additional tool is releasably lockable in at least one of its storing and working positions.

286

753. (New) The implement of Claim 752, wherein the at least one additional tool is lockable via a catch.

287

754. (New) The implement of Claim 752, further comprising an actuator for unlocking at least one of said additional tools.

288

755. (New) The implement of Claim 741, wherein slots are provided for said slide-action locking bars.

289

756. (New) The implement of Claim 752, wherein slots are provided for keys for releasably locking said tool.

290

757. (New) The implement of Claim 754, wherein the actuator is movable in a slot in one of the top and lateral surfaces of said member taking up said additional tool.

289

298

289

758. (New) The implement of Claim 754, wherein said actuator is operative to unlock a plurality of said additional tools.

292

239

759. (New) The implement of Claim 704, wherein said at least one additional tool comprises a tool selected from the group consisting of a scissors, a knife blade, a cutter, a staple remover, a screw driver, an extendable pointer, a magnifier, and a rule.

293

239

760. (New) The implement of Claim 704, wherein at least one of the members comprises adjacent channels extending in a longitudinal direction of the member, wherein in one of said channels functional elements of said stapler and said puncher, respectively, are disposed and wherein in at least one channel said additional tools are disposed.

294

239

761. (New) The implement of claim 704, wherein said elongated body is substantially closed.

295

239

762. (New) The implement of Claim 704, wherein the at least one additional tool is provided in the one of said first and second members comprising the staple anvil of said stapler and the hole die of said puncher, respectively.

296

239

763. (New) The implement of Claim 704, comprising means for releasably holding the first and second members in the first position.

297

296

764. (New) The implement of Claim 763, wherein said means comprises a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member.

298

765. (New) A multipurpose handheld implement comprising:

Sub
E1
a first and a second member, said first and second members being connected together to move between a first position, in which they form an elongated body, and a second position;

wherein said first and second members comprise at least one of the tools of a group consisting of a stapler and a puncher, said stapler comprising a staple magazine, a staple driver and a staple anvil of a stapler and said puncher comprising a punch, a hole die and a lever, said lever being positioned to actuate the punch;

wherein said first and second members when in the second position form an interspace to receive a workpiece for processing by one of the stapler and the puncher as the first and the second members are moved relative to each other;

wherein at least one of said members further comprises at least one additional tool in a storing position from which the at least one additional tool is movable into a working position; and

C4
wherein the member comprising the at least one additional tool comprises a hollow outer shell taking up the at least one additional tool in its storing position.

297 298
766. (New) The implement of Claim 765, wherein the first and second members each comprise a hollow outer shell with a circumferential contour defining a respective base surface.

300 299
767. (New) The implement of Claim 766, wherein the circumferential contours of the hollow shells of the first and second members when in the first position face one another.

301 299
768. (New) The implement of Claim 766, wherein the shells in said first position are arranged in substantial mirror symmetry so that the contours of the shells are substantially aligned.

302 299
769. (New) The implement of Claim 766, wherein each shell comprises a pair of substantially plane lateral surfaces extending substantially orthogonally to the base surface, and top and front surfaces having rounded contours.

303

298

770. (New) The implement of Claim 765, wherein one of said members has an outer contour comprising a flattened section.

304

298

771. (New) The implement of Claim 766, wherein in said first position the two base surfaces are spaced apart.

305

298

772. (New) The implement of Claim 766, wherein the shells in said first position are at least partly arranged in spaced apart relationship and in said first position form an interspace therebetween, said interspace being open to at least one end of the implement and forming a slot for material to be processed by said stapler and said puncher, respectively.

306

298

773. (New) The implement of Claim 765, wherein one of said first and second members in said first position is received at least partially in the other of said first and second members.

307

298

774. (New) The implement of Claim 765, wherein one of said members comprises a recess into which at least a part of the other of said members is displaceable.

308

308

775. (New) The implement of Claim 773, wherein, in said first position, respective outer contours of said members are substantially flush.

309

308

776. (New) The implement of Claim 773, wherein an insertion slot for receiving material to be processed is provided in the one of said first and second members comprising the staple anvil of said stapler.

310

308

777. (New) The implement of Claim 773, wherein an insertion slot for receiving material to be processed is provided in the one of said first and second members comprising the hole die of said puncher.

311

308

778. (New) The implement of Claim 769, wherein the lateral surfaces of at least one member are depressed relative to the contours of the top and front surfaces.

312

298

779. (New) The implement of Claim 766, wherein at least one of the members comprises a metallic core and a plastic cover cap mounted on said core.

313

342

780. (New) The implement of Claim 779, wherein said at least one core is U-shaped and comprises a U-base and a pair of U-legs, the U-base forming the base surface and the U-legs defining the lateral surfaces of the respective member.

314

302

781. (New) The implement of Claim 769, wherein at least one actuating element is disposed on at least one of the lateral surfaces.

313

314

782. (New) The implement of Claim 781, wherein the at least one actuating element is substantially flush with the contours of a top and end surface of the member provided with the at least one actuating element.

313

299

783. (New) The implement of Claim 766, wherein the members are interconnected adjacent a frontal surface by means of a pivot, the axis of which extends orthogonal to a longitudinal axis and parallel to the base surfaces of said members.

314

313

784. (New) The implement of Claim 783, wherein one of the members comprises a bearing bracket which extends into a hollow space of the other member wherein said pivot is disposed.

313

298

785. (New) The implement of Claim 765, wherein one of said members forms a lever-like actuator for the stapler.

314

298

786. (New) The implement of Claim 765, wherein one of said members forms a lever-like actuator for the puncher.

320

298

787. (New) The implement of Claim 765, wherein said members are spring biased into the second position which is defined by stops.

321

320

788. (New) The implement of Claim 787, wherein the stops are inactivatable.

322

298

789. (New) The implement of Claim 765, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein said locking element includes a manually operated actuator.

323

790. (New) The implement of Claim 789, wherein said actuator comprises a slider switch.

324

328

791. (New) The implement of Claim 789, wherein said actuator is disposed at a top surface of the one of said members including the locking element.

325

328

792. (New) The implement of Claim 789, wherein the members are interconnected by a pivot adjacent one end of the members, and wherein said actuator is disposed adjacent the other end of the members.

326

298

793. (New) The implement of Claim 765, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein the locking element is displaceable parallel to a top surface of the respective member.

327

298

794. (New) The implement of Claim 765, wherein a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member is provided, and wherein said other of said members comprises a bracket, and wherein the bracket comprises the locking receiver.

328

298

795. (New) The implement of Claim 765, further comprising means for selectively activating and deactivating the stapler.

329

298

796. (New) The implement of Claim 765, further comprising means for automatically deactivating the stapler after each stapling operation so that when the first and second members are in the first position after said stapling operation the stapler is inactive; and means for manually activating the stapler after deactivation by said deactivating means.

330

298

797. (New) The implement of Claim 765, wherein one of said members comprises a first activating mechanism for activating said stapler, and a second activating mechanism for releasing said latch; and wherein the first and second activating mechanisms are manually operable from at least one position external to said one of the members.

331

330

798. (New) The implement of Claim 797, wherein each of said first and second activating mechanisms comprises a manually operated actuator.

332

328

799. (New) The implement of Claim 795, wherein the first activating mechanism is located within an area adjacent to said staple driver.

333

331

800. (New) The implement of Claim 798, wherein said member comprises a top surface, a pair of lateral surfaces and a pair of end surfaces, the actuator for activating said stapler being provided at the end surface adjacent to the staple driver and the actuator for activating said latch being positioned at the top surface.

334

298

801. (New) The implement of Claim 765, wherein at least one of said members is provided with a cavity for receiving said at least one additional tool in its storing position.

335

298

802. (New) The implement of Claim 765, wherein the at least one additional tool is slideably disposed in at least one of the members.

336

335

803. (New) The implement of Claim 802, wherein the at least one additional tool comprises a slide-action locking bar which is actuatable from the exterior.

337

298

804. (New) The implement of Claim 765, wherein a plurality of additional tools are disposed parallel to a longitudinal extension of the members.

338

335

805. (New) The implement of Claim 802, wherein the at least one member comprises slots at at least one of its end surfaces, said at least one additional tool being slidable through said slots into its working positions.

339

335

806. (New) The implement of Claim 802, wherein said at least one additional tool has a guiding shank provided at its rear end with respect to the telescoping direction.

340

339

807. (New) The implement of Claim 806, wherein a longitudinal guide for said guiding shank is provided.

341

340

808. (New) The implement of Claim 807, wherein the guiding shank is provided with a sliding block.

348

335

809. (New) The implement of Claim 802, wherein the at least one additional tool is slidable along one of its top and lateral surfaces of the corresponding member.

349

298

810. (New) The implement of Claim 765, wherein the at least one additional tool is pivotably connected with the at least one of said members such that it is pivotable out of said member into its working position.

344

298

811. (New) The implement of Claim 765, wherein at least one removable tool is disposed in at least one of the members and is removable from said member.

345

298

812. (New) The implement of Claim 765, wherein the at least one additional tool is spring-biased in at least one of its storing and working positions.

346

298

813. (New) The implement of Claim 765, wherein the at least one additional tool is releasably lockable in at least one of its storing and working positions.

347

346

814. (New) The implement of Claim 813, wherein the at least one additional tool is lockable via a catch.

348

348

815. (New) The implement of Claim 813, further comprising an actuator for unlocking at least one of said additional tools.

349

335

816. (New) The implement of Claim 802, wherein slots are provided for said slide-action locking bars.

350

346

817. (New) The implement of Claim 813, wherein slots are provided for keys for releasably locking said tool.

351

348

818. (New) The implement of Claim 815, wherein the actuator is movable in a slot in one of the top and lateral surfaces of said member taking up said additional tool.

352

348

819. (New) The implement of Claim 815, wherein said actuator is operative to unlock a plurality of said additional tools.

353

298

820. (New) The implement of Claim 765, wherein said at least one additional tool comprises a tool selected from the group consisting of a scissors, a knife blade, a cutter, a staple remover, a screw driver, an extendable pointer, a magnifier, and a rule.

354

298

821. (New) The implement of Claim 765, wherein at least one of the members comprises adjacent channels extending in a longitudinal direction of the member, wherein in one of said channels functional elements of said stapler and said puncher, respectively, are disposed, and wherein in at least one channel said additional tools are disposed.

355

298

822. (New) The implement of claim 765, wherein said elongated body is substantially closed.

356

298

823. (New) The implement of Claim 765, wherein the at least one additional tool is provided in the one of said first and second members comprising the staple anvil of said stapler and the hole die of said puncher, respectively.

357

298

824. (New) The implement of Claim 765, comprising means for releasably holding the first and second members in the first position.

358

354

825. (New) The implement of Claim 824, wherein said means comprises a latch comprising a displaceable locking element in one of the members and a locking receiver in the other member.